## Technical Specifications

Decking	Promenade	Paramount®	Concordia™ Symmetry®	Concordia™ Horizon®	Sanctuary®	Good Life
Board Profile Dimensions	Flat bottom 1 in. x 5.5 in.	Flat bottom 1 in. x 5.5 in.	Flat bottom .935 in. x 5.4 in.	Flat bottom .935 in. x 5.4 in.	Flat bottom .925 in. x 5.25 in.	Relief bottom .93 in. x 5.25 in.
Square-Edge Profile						
Grooved-Edge Profile						<b></b>
Reversible	No	No	Yes	Yes	No	No
Material	Cellular Foam Polymer with co-extruded cap on 4 sides	Cellular Foam Polymer with co-extruded cap on 3 sides	Wood-plastic composite core with co-extruded PermaTech cap on 4 sides	Wood-plastic composite core with co-extruded PermaTech cap on 4 sides	Wood-plastic composite core with co-extruded PermaTech cap on 3 sides	Wood-plastic composite core with co-extruded cap on 3 sides
Multi-Tonal	Natural Reef, Rus- set Dune, Sandy Pier, Shaded Cay, Weathered Cliff and Moonlit Cove	Brownstone, Flagstone and Sandstone	Burnt Umber, Cin- nabar, Graphite and Warm Sienna	Ipe, Castle Gray, Rosewood and Tudor Brown	Espresso, Latte, Earl Grey, Morin- ga and Chai	Beach House, Bungalow and Tuscan Villa
Solid Colors	N/A	Mineral	N/A	N/A	N/A	Cabin and Cottage
Limited Performance Warranty	Lifetime	Lifetime	Lifetime	Lifetime	40-Year	Escapes 30-Year Weekender 25- Year
Stain and Fade Warranty	50-Year	50-Year	50-Year	50-Year	40-Year	Escapes 30-Year Weekender 25- Year
Square-Edge Lengths	16 and 20 ft.	16 and 20 ft.	12, 16 and 20 ft.	12, 16 and 20 ft.	16 and 20 ft.	16 and 20 ft.
Grooved-Edge Lengths	12, 16 and 20 ft.	12, 16 and 20 ft.	12, 16 and 20 ft.	12, 16 and 20 ft.	12, 16 and 20 ft.	12, 16 and 20 ft.
Span Limitations						
Perpendicular to joist:	16 in.	16 in.	16 in.	16 in.	16 in.	16 in.
Up to 45° angle to joist:	12 in.	12 in.	12 in.	12 in.	12 in.	12 in.
Stair tread spacing:	24 in.**	24 in.**	12 in.	12 in.	12 in.	12 in.
Fascia Available	.50 in. x 11.75 in. x 12 ft. Matching colors	.50 in. x 11.75 in. x 12 ft. Complementary colors	.75 in. x 11.25 in. x 12 ft. Matching colors	.75 in. x 11.25 in. x 12 ft. Matching colors	.75 in. x 11.25 in. x 12 ft. Matching colors	.75 in. x 11.25 in. x 12 ft. Matching colors
Risers Available	No	No	.75 in. x 7.25 in. x 12 ft. All colors	.75 in. x 7.25 in. x 12 ft. All colors	.75 in. x 7.25 in. x 12 ft. All colors	No

Railing	Brio™ Rhythm	HavenView™ CountrySide	HavenView™ CitySide
Profile Dimensions	Top Rail: 3.5 in. x 1.75 in. Bottom Rail: 3.5 in. x 1.75 in.	Top Rail: 3 in. x 3 in. Bottom Rail: 2.5 in. x 2 in.	Top Rail: 2.25 in. x 1.71 in. Bottom Rail: 1.32 in. x 1.31 in.
Material	Premium quality composite with permanent PVC surface	Premium quality composite with permanent PVC surface	Aluminum
Colors	Tranquil White, Simply Brown and Serene Black	Tranquil White, Simply Brown and Serene Black	Matte Black
Limited Performance Warranty	25-Year	25-Year	25-Year
Line / Stair Sections	6 ft. and 8 ft.	6 ft. and 8 ft.	6 ft. and 8 ft.
Rail Heights	36-in. or 42-in. rail heights	36-in. or 42-in. rail heights	36-in. rail height
Post Sleeve Kit Components also sold separately. See page 32 for details.	Post sleeve: 5 in. x 5 in. x 39 in., 45 in. or 108 in. Post cap: 5 in. x 5 in. Post skirt: 5 in. x 5 in.	Post sleeve: 5 in. x 5 in. x 39 in., 45 in. or 108 in. Post cap: 5 in. x 5 in. Post skirt: 5 in. x 5 in.	Post: 2.5 in. x 2.5 in. x 38.5 in. (including cap). Posts kits include cap and skirt. 5 in. x 5 in. Fiberon composite posts may also be used with CitySide railing.
Available Baluster Styles, Profiles and Dimensions	Square Composite: 1.25 x 1.25 x 33.5 in. or 1.25 x 1.25 x 39.5 in. for line or stairs	Beveled Composite: 1.25 x 1.25 x 29.5 in. or 1.25 x 1.25 x 35.5 in. Round Aluminum (Black): .75 in. diameter x 29.5 in. and 35.5 in. for line or 30 in. and 36 in. for stairs	Balusters: .625 x .625 x 31.88 in. square aluminum


See your Fiberon seller or visit www.fiberondecking.com for details on limited warranties and exclusions.



## WARNING:

Drilling, sawing, or machining wood-composite products containing wood fiber can expose you to wood dust, a substance known to the State of California to cause cancer.

Avoid inhaling dust generated from wood-composite products or use a dust mask or other safeguards for personal protection. For more information, go to www.P65Warnings.ca.gov.



<sup>\*</sup>Available for special order in 12 ft. 
\*\*When installing Promenade or Paramount PVC decking, secure stair treads over and in contact with a treated pine 2x6, installed flat, not on edge, as under support and secured with Simpson A23 approved connectors and  $10d \times 1-1/2$  in. hot galvanized nails.